SIEMENS

## Data sheet 6AG1132-4HB13-2AB0




Figure similar

SIPLUS ET 200S EM 2DQ RLY 5 A based on 6ES7132-4HB13-0AB0 with conformal coating, -40…+60 °C, 24 V-48 V DC/5 A, 24 V-230 V AC/5 A 15 mm width,substitute value output 5 units per packing unit

| | |
|---|---|
| **General information** | |
| Product function | |
| ● Isochronous mode | No |
| **Supply voltage** | |
| Load voltage L+ | |
| ● Rated value (DC) | 24 V; From power module |
| ● Reverse polarity protection | Yes |
| **Input current** | |
| from load voltage L+ (without load), max. | 30 mA |
| from backplane bus 3.3 V DC, max. | 10 mA |
| **Power loss** | |
| Power loss, typ. | 0.6 W |
| **Address area** | |
| Address space per module | |
| ● Address space per module, max. | 1 byte |
| ● with packing | 2 bit |
| **Digital outputs** | |
| Type of digital output | Relays |
| Number of digital outputs | 2 |
| Short-circuit protection | No |
| Limitation of inductive shutdown voltage to | No |
| Controlling a digital input | Yes |
| Output current | |
| ● for signal "1" rated value | 5 A |
| ● for signal "1" minimum load current | 8 mA |
| Switching frequency | |
| ● with resistive load, max. | 2 Hz |
| ● with inductive load, max. | 0.5 Hz |
| ● on lamp load, max. | 2 Hz |
| Relay outputs | |
| Switching capacity of contacts | |
| — Thermal continuous current, max. | 5 A |
| Cable length | |
| ● shielded, max. | 1 000 m |
| ● unshielded, max. | 600 m |
| **Interrupts/diagnostics/status information** | |
| Diagnostics function | No |
| Substitute values connectable | Yes; 0/1 |


© Copyright Plcbin

| | |
|---|---|
| Diagnostics indication LED | |
| ● Status indicator digital output (green) | Yes |
| **Potential separation** | |
| Potential separation digital outputs | |
| ● between the channels | Yes |
| ● between the channels and backplane bus | Yes |
| ● Between the channels and load voltage L+ | Yes |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | -40 °C; = Tmin |
| ● max. | 60 °C; = Tmax |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 2 000 m |
| ● Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) |
| Relative humidity | |
| ● With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; incl. condensation / frost permitted (no commissioning under condensation conditions) |
| Resistance | |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
| **Dimensions** | |
| Width | 15 mm |
| Height | 81 mm |
| Depth | 52 mm |
| **Weights** | |
| Weight, approx. | 50 g |
| **Classifications** | |

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-26-04 |
| eClass | 14 | 27-24-26-04 |
| eClass | 12 | 27-24-26-04 |
| eClass | 9.1 | 27-24-26-04 |
| eClass | 9 | 27-24-26-04 |
| eClass | 8 | 27-24-26-04 |
| eClass | 7.1 | 27-24-26-04 |
| eClass | 6 | 27-24-26-04 |
| ETIM | 10 | EC001599 |
| ETIM | 9 | EC001599 |


© Copyright Plcbin

| | | |
|---|---|---|
| ETIM | 8 | EC001599 |
| ETIM | 7 | EC001599 |
| IDEA | 4 | 3566 |
| UNSPSC | 15 | 32-15-17-05 |

## Approvals / Certificates

| General Product Approval | | | | | EMV |
|---|---|---|---|---|---|
| China RoHS | Manufacturer Declaration | CE EG-Konf. | UKCA | EAC | RCM |

**last modified:** 4/4/2025


Subject to change without notice
© Copyright Plcbin