SIEMENS

## Data sheet 6AG1193-4CB70-7AA0



Figure similar

***spare part*** SIPLUS ET 200S TM-E15N24-0 based on 6ES7193-4CB70-0AA0 with conformal coating, -40…+70 °C, 5 units per packing unit, for electronic modules, 15 mm width, FastConnect terminal, 2x4 terminal connections without terminal access to AUX1, AUX1 continuous

| | |
|---|---|
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | -40 °C; = Tmin |
| ● max. | 70 °C; = Tmax |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 5 000 m |
| ● Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity | |
| ● With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state) |
| Resistance | |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
| **Dimensions** | |
| Width | 15 mm |
| Height | 162 mm |


Subject to change without notice
© Copyright Plcbin

| | |
|---|---|
| Depth | 43 mm |
| **Weights** | |
| Weight, approx. | 72 g |
| **Scope of supply** | |
| Delivery quantity in pieces | 5 |
| **Classifications** | |

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-26-03 |
| eClass | 14 | 27-24-26-03 |
| eClass | 12 | 27-24-26-03 |
| eClass | 9.1 | 27-24-26-03 |
| eClass | 9 | 27-24-26-03 |
| eClass | 8 | 27-24-26-03 |
| eClass | 7.1 | 27-24-26-03 |
| eClass | 6 | 27-24-26-03 |
| ETIM | 10 | EC001598 |
| ETIM | 9 | EC001598 |
| ETIM | 8 | EC001598 |
| ETIM | 7 | EC001598 |
| IDEA | 4 | 3560 |
| UNSPSC | 15 | 32-15-17-04 |

**Approvals / Certificates**

| General Product Approval | | | | EMV | |
|---|---|---|---|---|---|
| CE EG-Konf. | UKCA | Manufacturer Declaration | China RoHS | | RCM |

**For use in hazardous locations**

CCC-Ex

**last modified:** 3/12/2024


Subject to change without notice
© Copyright Plcbin