SIEMENS

Data sheet 6AG1208-0BA00-7AC2



SIPLUS NET SCALANCE XC208 based on 6GK5208-0BA00-2AC2 with conformal coating, -40…+70 °C, manageable layer 2 IE switch; 8x 10/100 Mbps RJ45 ports; 1x console port; diagnostics LEDs redundant power supply temperature range -40 °C to +70 °C; assembly: DIN rail/S7 mounting rail/wall office redundancy functions features (RSTP, VLAN,etc.); PROFINET IO device Ethernet/IP-compliant C-Plug slot;

product type designation	
product brand name	SIPLUS
product type designation	XC208
Technical Product Detail Page	https://www.plcbin.com/?s=6AG1208-0BA00-7AC2
transfer rate	
transfer rate	10, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
● for network components or terminal equipment	8; RJ45
number of 10/100 Mbit/s RJ45 ports	
● with securing collar	8
interfaces / other	
number of electrical connections	
● for operator console	1
● for signaling contact	1
● for power supply	1
type of electrical connection	
● for operator console	RJ11
● for signaling contact	2-pole terminal block
● for power supply	4-pole terminal block
design of the removable storage	
● C-PLUG	Yes
operating voltage / of the signaling contacts	
● at DC / rated value	24 V
operational current / of the signaling contacts	
● at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
type of voltage / 1 / of the supply voltage	DC
● supply voltage / 1 / rated value	24 V
● power loss [W] / 1 / rated value	4.2 W
● supply voltage / 1 / voltage range	9.6 ... 31.2
ambient conditions	
ambient temperature / in horizontal mounting position / during operation	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
relative humidity	
● with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets

© Copyright Plcbin

ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
resistance to biologically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna); class 3B3 on request
● conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
● conformity according to EN 60721-3-6	Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (Severity degree 3); *
resistance to mechanically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust; *
● conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
environmental category / according to IEC 60721 / note	* The supplied plug covers must remain in place on the unused interfaces during operation!
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
design	compact
width	60 mm
height	147 mm
depth	125 mm
net weight	0.52 kg
material / of the enclosure	Polycarbonate (PC-GF10) / pressure die cast aluminum
fastening method	
● 35 mm DIN-rail mounting	Yes
● wall mounting	Yes
● S7-300 rail mounting	Yes
● S7-1500 rail mounting	Yes
product features, product functions, product components / general	
cascading in the case of a redundant ring / at reconfiguration time of <\~0.3\~s	50
cascading in cases of star topology	any (depending only on signal propagation time)
product function	
● QoS according to DSCP	Yes
product feature	
● Cut Through switching method	No
● Store & Forward switching method	Yes
product functions / management, configuration, engineering	
product function	
● CLI	Yes
● web-based management	Yes
● MIB support	Yes
● TRAPs via email	Yes
● configuration with STEP 7	Yes
● RMON	Yes
● SMTP server	No
● port mirroring	Yes
● multiport mirroring	Yes
● CoS	Yes
● PROFINET IO diagnosis	Yes
● switch-managed	Yes
PROFINET conformity class	B

© Copyright Plcbin

telegram length / for Ethernet / maximum	1632 byte
protocol / is supported	
● Telnet	Yes
● HTTP	Yes
● HTTPS	Yes
● TFTP	Yes
● SFTP	Yes
● BOOTP	No
● GMRP	Yes
● DCP	Yes
● LLDP	Yes
● EtherNet/IP	Yes
● SNMP v1	Yes
● SNMP v2	Yes
● SNMP v3	Yes
● IGMP (snooping/querier)	Yes
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function	
● port diagnostics	Yes
● statistics Packet Size	Yes
● statistics packet type	Yes
● error statistics	Yes
● SysLog	Yes
product functions / VLAN	
product function	
● VLAN - port based	Yes
● VLAN - protocol-based	No
● VLAN - IP-based	No
number of VLANs / maximum	257
number of VLANs - dynamic / maximum	257
number of VLANs / at ring redundancy (HRP; MRP; standby link)	257
product functions / DHCP	
product function	
● DHCP server	Yes
● DHCP client	Yes
● DHCP Option 82	Yes
● DHCP Option 66	Yes
● DHCP Option 67	Yes
product functions / redundancy	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
● media redundancy protocol (MRP) with redundancy manager	Yes
● of the PROFINET IO device / is supported / H-Sync forwarding	Yes
● of the PROFINET IO device / is supported / PROFINET system redundancy	Yes
● ring redundancy	Yes
● high speed redundancy protocol (HRP) with redundancy manager	Yes
● high speed redundancy protocol (HRP) with standby redundancy	Yes
● redundancy procedure STP	Yes
● redundancy procedure RSTP	Yes
● redundancy procedure MSTP	Yes
● Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes

© Copyright Plcbin

● Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
● passive listening	Yes
protocol / is supported	
● LACP	Yes
system modification during operation	
product function / configuration in RUN via CiR/H-CiR	Yes
product functions / security	
product function	
● IEEE 802.1x (radius)	Yes
● RADIUS client	Yes
● broadcast/multicast/unicast limiter	Yes
● broadcast blocking	Yes
protocol / is supported	
● SSH	Yes
● SSL	Yes
product functions / time	
product function	
● SICLOCK support	Yes
● NTP-client	Yes
● SNTP client	Yes
protocol / is supported	
● NTP	Yes
● SNTP	Yes
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
product conformity / according to EMC-guideline	2014/30/EU
standard	
● for EMC interference emission	EN 61000-6-4, EN 50121-4
● for immunity to EMC	EN 61000-6-2, EN 50121-4
standards, specifications, approvals / other	
certificate of suitability	
● railway application in accordance with EN 50121-4	Yes
● RoHS conformity	Yes
product functions / general	
MTBF	48 a
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://www.plcbin.com/?s=6AG1208-0BA00-7AC2
● to web page: selection aid TIA Selection Tool	https://www.plcbin.com/?s=6AG1208-0BA00-7AC2
● to website: Industrial communication	https://www.plcbin.com/?s=6AG1208-0BA00-7AC2
● to web page: SiePortal	https://www.plcbin.com/?s=6AG1208-0BA00-7AC2
● to website: Image database	https://www.plcbin.com/?s=6AG1208-0BA00-7AC2
● to website: CAx-Download-Manager	https://www.plcbin.com/?s=6AG1208-0BA00-7AC2
● to website: Industry Online Support	https://www.plcbin.com/?s=6AG1208-0BA00-7AC2
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are

© Copyright Plcbin

no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.plcbin.com/?s=6AG1208-0BA00-7AC2 . (V4.7)

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

China RoHS

General Product Approval

EMV

last modified: 3/10/2026

© Copyright Plcbin