SIEMENS

Data sheet 6AV6671-5CE00-0AX1



**** Spare part *** Does not correspond to the current version of the standard. Charging station for Mobile Panel 277(F) IWLAN With lock For charging and storing the Mobile Panel 277(F) IWLAN Charging of 2 additional batteries

Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	3.2 A
Power	
Active power input, typ.	77 W
Degree and class of protection	
IP degree of protection	IP65
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
Ambient conditions	
Ambient temperature during operation	
Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	40 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	85 %
Dimensions	
Width	208 mm
Height	333 mm
Depth	75 mm
Weights	
Weight (without packaging)	1.1 kg
Classifications	

	Version	Classification
eClass	16	27-33-02-92
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92

© Copyright Plcbin

eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

Manufacturer Declaration





last modified: 5/22/2024

© Copyright Plcbin