SIEMENS

Data sheet 6AV6881-0AG11-0AA0

service set KTP Mobile, combination cross-tip neck screw scope of supply: 5 screws



Figure similar

General information	
Product type designation	Mobile Panel M3 screw
Standards, approvals, certificates	
CE mark	No; No CE marking obligation
RoHS conformity	Yes; unnecessary
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	No; possible under certain conditions
Ambient temperature during operation	
● min.	0 °C
● max.	55 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Relative humidity	
● Operation, max.	95 %
Mechanics/material	
Material	general requirement according to DIN ISO 8992
Screw type	
● Cross-tip	Yes; Cross-tip including slot
Dimensions	
Height	12 mm; Overall
Depth	10 mm; Up to underside of screw head
Thickness	11 mm; Screw head
Weights	
Weight (without packaging)	2.2 g
Weight (with packaging)	4.1 g
Scope of supply	
Delivery quantity in pieces	5; Combination cross-tip collar screw (M3x10)
Components included	Screws for attachment
Other	
Merchandise	No
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Target devices	Wired Mobile Panel (PROFIBUS and PROFINET)
Note:	Observe documentation of the target device
Classifications	

© Copyright Plcbin

	Version	Classification
eClass	16	27-33-02-92
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415

https://www.plcbin.com/?s=6AV6881-0AG11-0AA0

last modified: 10/6/2024

© Copyright Plcbin