SIEMENS

## Data sheet 6AV6881-6UD41-0AA0

adapter frame widescreen for 19" touch devices, so that small 19" devices fit into the installation cutout of large 19" widescreen devices, scope of supply: 1 adapter frame including mounting accessories



Figure similar

| | |
|---|---|
| **General information** | |
| Product type designation | Adapter frame 19" touch widescreen |
| **Installation type/mounting** | |
| Mounting in portrait format possible | Yes |
| Mounting in landscape format possible | Yes |
| **Standards, approvals, certificates** | |
| CE mark | No; No CE marking obligation |
| REACH | Yes; Tested |
| RoHS conformity | Yes; Tested / compliant |
| Use in hazardous areas | |
| ● ATEX Zone 2 | No |
| ● ATEX Zone 22 | No |
| ● ATEX as target device | No |
| ● IECEx Zone 1 | No |
| ● IECEx Zone 11 | No |
| ● IECEx Zone 2 | No |
| ● IECEx Zone 22 | No |
| ● cULus Class I Zone 1 | No |
| ● cULus Class I Zone 2, Division 2 | No |
| ● cULus Class II Division 2 | No |
| ● FM Class I Division 2 | No |
| ● FM Class II Division 2 | No |
| Marine approval | |
| ● Germanischer Lloyd (GL) | No |
| ● American Bureau of Shipping (ABS) | No |
| ● Bureau Veritas (BV) | No |
| ● Det Norske Veritas (DNV) | No |
| ● Korean Register of Shipping (KRS) | No |
| ● Lloyds Register of Shipping (LRS) | No |
| ● Nippon Kaiji Kyokai (Class NK) | No |
| ● Polski Rejestr Statkow (PRS) | No |
| ● Chinese Classification Society (CCS) | No |
| ● Marine approval as target device | No |
| **Ambient conditions** | |
| Suited for indoor use | Yes |
| Suited for outdoor use | No |
| Ambient temperature during operation | |
| ● min. | 0 °C |


© Copyright Plcbin

| | |
|---|---|
| ● max. | 50 °C |
| Ambient temperature during storage/transportation | |
| ● min. | -20 °C |
| ● max. | 60 °C |
| Relative humidity | |
| ● Operation, max. | 90 % |
| **Accessories** | |
| Function description | mechanical adapter |
| belongs to product | MTP1900 Unified Comfort, ITC1900 V3 |
| **Mechanics/material** | |
| Enclosure material (front) | |
| ● Aluminum | Yes; Powder-coated |
| **Dimensions** | |
| Width | 480.2 mm |
| Height | 334.2 mm |
| Depth | 33 mm |
| Mounting cutout, width | 465.2 mm; existing mounting cut-out |
| Mounting cutout, height | 319.2 mm; existing mounting cut-out |
| mounting depth | 25 mm |
| **Scope of supply** | |
| Delivery quantity in pieces | 1; Adapter frame 19" |
| Components included | incl. mounting accessories |
| **Other** | |
| Merchandise | No |
| Manufacturer name | SIEMENS AG |
| Manufacturer's address | Gleiwitzerstraße 555, 90475 Nuremberg, Germany |
| Note: | observe the user manual |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-33-02-92 |
| eClass | 14 | 27-33-02-92 |
| eClass | 12 | 27-33-02-92 |
| eClass | 9.1 | 27-33-02-92 |
| eClass | 9 | 27-33-02-92 |
| eClass | 8 | 27-24-92-03 |
| eClass | 7.1 | 27-24-92-03 |
| eClass | 6 | 27-24-92-03 |
| ETIM | 10 | EC002584 |
| ETIM | 9 | EC002584 |
| ETIM | 8 | EC002584 |
| ETIM | 7 | EC002584 |

**Approvals / Certificates**

| General Product Approval | For use in hazardous locations | | | | |
|---|---|---|---|---|---|
| UL | UL | IECEx | Miscellaneous | FM | CCC-Ex |

| For use in hazardous locations | | |
|---|---|---|
| ATEX | IECEx | Miscellaneous |


© Copyright Plcbin

## Further information

**Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415**

https://www.plcbin.com/?s=6AV6881-6UD41-0AA0

**last modified:** 8/1/2024


© Copyright Plcbin