SIEMENS

Data sheet 6ES7134-4MB02-0AB0



*** Spare part *** SIMATIC DP, Electronics module 2 AI I High Feature for ET 200S, 15 mm width, Cycle time per module: 0.5 ms, +/-20mA; 15 bit+sign, 4.. 20mA; 15 bit, Operational limit +/-0.1% with SF LED (group fault)

General information	
Product function	
● Isochronous mode	Yes
Supply voltage	
Load voltage L+	
● Rated value (DC)	24 V
● Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	48 mA
from backplane bus 3.3 V DC, max.	10 mA
Output voltage	
Power supply to the transmitters	
● present	Yes
● short-circuit proof	Yes
Power loss	
Power loss, typ.	1.2 W
Address area	
Address space per module	
● Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2
permissible input current for current input (destruction limit), max.	50 mA
Cycle time (all channels) max.	0.5 ms; 0.5 ms for 2 channels without noise suppression, 18 / 21 ms per channel with noise suppression
Input ranges (rated values), currents	
● -20 mA to +20 mA	Yes
● 4 mA to 20 mA	Yes
Cable length	
● shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
● Interference voltage suppression for interference frequency f1 in Hz	60 / 50 Hz / no
● Conversion time (per channel)	0.04 ms; Without noise suppression 17/20 ms per channel with error
Smoothing of measured values	
● Parameterizable	Yes; In 4 stages: 1x, 4x, 16x, 32x cycle time

© Copyright Plcbin

● Step: None	Yes; 1x
● Step: low	Yes; 4x
● Step: Medium	Yes; 16x
● Step: High	Yes; 32x
Encoder	
Connection of signal encoders	
● for current measurement as 2-wire transducer	
— Burden of 2-wire transmitter, max.	750 Ω
Errors/accuracies	
Operational error limit in overall temperature range	
● Current, relative to input range, (+/-)	0.1 %; 0.2% without interference frequency suppression
Basic error limit (operational limit at 25 °C)	
● Current, relative to input range, (+/-)	0.05 %; 0.1% without interference frequency suppression
Interrupts/diagnostics/status information	
Alarms	
● Hardware interrupt	Yes
Diagnoses	
● Wire break	Yes; Measuring range 4 to 20 mA only
● Group error	Yes
● Overflow/Underflow	Yes
Diagnostics indication LED	
● Group error SF (red)	Yes
Potential separation	
Potential separation analog inputs	
● between the channels	No; however, increased permissible potential difference between the inputs.
● between the channels and backplane bus	Yes
● Between the channels and load voltage L+	Yes
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	45 g

Classifications

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Manufacturer Declaration

Miscellaneous

Metrological Approval

© Copyright Plcbin

General Product Approval					EMV
RCM	EAC	China RoHS	CE EG-Konf.	UKCA	RCM

For use in hazardous locations					
ATEX	FM	ATEX	UL	ATEX	IECEx

For use in hazardous locations		Maritime application			
Miscellaneous	CCC-Ex	ABS	BUREAU VERITAS	DNV	LRS

Maritime application			
NK / Nippon Kaiji Kyokai	PRS	RINA	CCS (China Classification Society)

last modified: 8/22/2025

© Copyright Plcbin