SIEMENS

Data sheet 6ES7135-6HB00-0CA1



SIMATIC ET 200SP, Analog output module, AQ 2x U/I High Feature suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.1%

General information	
Product type designation	AQ 2xU/I HF
HW functional status	from FS21
Firmware version	V1.0.3
● FW update possible	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color-coded label	CC00
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	Yes; 250 µs
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V13 / V13
● STEP 7 configurable/integrated from version	V5.5 SP3 / -
● PCS 7 configurable/integrated from version	V8.1 SP1
● PROFIBUS from GSD version/GSD revision	GSD Revision 5
● PROFINET from GSD version/GSD revision	GSDML V2.3
Operating mode	
● Oversampling	No
● MSO	No
CiR - Configuration in RUN	
Reparameterization possible in RUN	No
Calibration possible in RUN	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	45 mA; without load
Current consumption, max.	90 mA; 2 channels current output 20 mA
Power loss	
Power loss, typ.	0.9 W
Address area	
Address space per module	
● Address space per module, max.	4 byte; + 1 byte for QI information
Hardware configuration	

© Copyright Plcbin

Automatic encoding	Yes
● Mechanical coding element	Yes
● Type of mechanical coding element	Type A
Analog outputs	
Number of analog outputs	2
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	45 mA
Cycle time (all channels), min.	750 µs
Output ranges, voltage	
● 0 to 10 V	Yes; 15 bit
● 1 V to 5 V	Yes; 13 bit
● -5 V to +5 V	Yes; 15 bit incl. sign
● -10 V to +10 V	Yes; 16 bit incl. sign
Output ranges, current	
● 0 to 20 mA	Yes; 15 bit
● -20 mA to +20 mA	Yes; 16 bit incl. sign
● 4 mA to 20 mA	Yes; 14 bit
Connection of actuators	
● for voltage output two-wire connection	Yes
● for voltage output four-wire connection	Yes
● for current output two-wire connection	Yes
Load impedance (in rated range of output)	
● with voltage outputs, min.	2 kΩ
● with voltage outputs, capacitive load, max.	1 µF
● with current outputs, max.	500 Ω
● with current outputs, inductive load, max.	1 mH
Destruction limits against externally applied voltages and currents	
● Voltages at the outputs	30 V
Cable length	
● shielded, max.	1 000 m; 200 m for voltage output
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
Settling time	
● for resistive load	0.05 ms
● for capacitive load	0.05 ms; Max. 47 nF and 20 m cable length
● for inductive load	0.05 ms
Errors/accuracies	
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.03 %
Temperature error (relative to output range), (+/-)	0.003 %/K
Crosstalk between the outputs, max.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.03 %
Operational error limit in overall temperature range	
● Voltage, relative to output range, (+/-)	0.2 %
● Current, relative to output range, (+/-)	0.2 %
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to output range, (+/-)	0.1 %
● Current, relative to output range, (+/-)	0.1 %
Isochronous mode	
Execution and activation time (TCO), min.	500 µs
Bus cycle time (TDP), min.	750 µs
Jitter, max.	5 µs
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	

© Copyright Plcbin

● Diagnostic alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	Yes; channel-by-channel, only for output type "current"
● Short-circuit	Yes; channel-by-channel, only for output type "voltage"
● Group error	Yes
● Overflow/Underflow	Yes; channel by channel
Diagnostics indication LED	
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red LED
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	28.6 kg
— global warming potential, (during production) [CO2 eq]	5.33 kg
— global warming potential, (during operation) [CO2 eq]	23.6 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.343 kg
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C; < 0 °C as of FS04
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C; < 0 °C as of FS04
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP System Manual
Absolute humidity	
● dew point, min.	-60 °C; suitable for dry room applications
Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	31 g

Classifications

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01

© Copyright Plcbin

ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration | Metrological Approval

General Product Approval

China RoHS

For use in hazardous locations

FM | CCC-Ex | Type Examination Certificate

For use in hazardous locations

Miscellaneous | CCC-Ex

Maritime application

NK / Nippon Kaiji Kyokai | CCS (China Classification Society) | KR (Korean Register of Shipping)

Maritime application

Environment

Environment

last modified: 2/1/2026

© Copyright Plcbin