SIEMENS

Data sheet 6ES7138-4HA00-0AB0



*** spare part *** SIMATIC DP,DP master interface for IM151-7 CPU or IM151-8 PN/DP (ET200S), module with PROFIBUS DP interface (9-pole D-sub socket) as DP master

Interfaces	
PROFIBUS DP	
● Transmission rate, max.	12 Mbit/s; 9,6 / 19,2 / 45,45 / 93,75 / 187,5 / 500 kbit/s; 1,5 / 3 / 6 / 12 Mbit/s
● Cable length, max.	100 m; Shielded
Protocols	
PROFIBUS DP	Yes
Dimensions	
Width	35 mm
Height	119.5 mm
Depth	75 mm
Weights	
Weight, approx.	100 g

Classifications

	Version	Classification
eClass	16	27-24-26-08
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Manufacturer Declaration

EG-Konf.

UK CA

Miscellaneous

UL

RCM

Subject to change without notice
© Copyright Plcbin

General Product Approval					EMV
EAC	Manufacturer Declaration	China RoHS	CE EG-Konf.	UKCA	RCM

For use in hazardous locations					
ATEX	FM	ATEX	UL	Miscellaneous	ATEX

For use in hazardous locations		Maritime application			
IECEx	CCC-Ex	ABS	BUREAU VERITAS	DNV	LRS

Maritime application			
NK / Nippon Kaiji Kyokai	PRS	RINA	CCS (China Classification Society)

last modified: 7/17/2025

© Copyright Plcbin