SIEMENS

Data sheet 6ES7193-6AM00-0AA0

Siemens EcoTech

SIMATIC BusAdapter BA 2xM12, 2 x M12 push-pull sockets, D-coding, also suitable for standard M12



General information	
Product type designation	BA 2x M12
Interfaces	
Number of PROFINET interfaces	1; 2 ports (switch) 2x M12
Supports protocol for PROFINET IO	
● Number of M12 ports	2
Cable length	
— Cu conductors	100 m
Standards, approvals, certificates	
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	1.14 kg
— global warming potential, (during production) [CO2 eq]	1.2 kg
— global warming potential, (during operation) [CO2 eq]	0 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.069 kg
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C; No condensation
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C; No condensation
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual
Dimensions	
Width	20 mm
Height	73.5 mm
Depth	59 mm
Weights	
Weight, approx.	59 g
Classifications	

	Version	Classification

Subject to change without notice
© Copyright Plcbin

eClass	16	27-24-26-92
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

General Product Approval

Test Certificates

Special Test Certific-ate

Type Test Certific-ates/Test Report

Maritime application

Maritime application

other

Miscellaneous

Confirmation

other

Miscellaneous

Railway

Confirmation

Special Test Certific-ate

Environment

Environmental Con-firmations

last modified: 9/19/2025

© Copyright Plcbin