SIEMENS

## Data sheet 6ES7193-6SC20-1AM0



SIMATIC ET 200SP, set for 5 shield connections, with 5 shield terminals, 5 shield supports, 5 support elements

| | |
|---|---|
| **General information** | |
| Product type designation | Shield connection |
| **Installation type/mounting** | |
| Mounting | can be plugged into ET 200SP BaseUnit |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | -40 °C |
| ● max. | 70 °C |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 5 000 m |
| Absolute humidity | |
| ● dew point, min. | -60 °C; suitable for dry room applications |
| **Mechanics/material** | |
| Material | Brass, nickel-plated |
| **Dimensions** | |
| Width | 15 mm |
| Height | 14 mm |
| Depth | 80 mm |
| **Classifications** | |

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-26-92 |
| eClass | 14 | 27-24-26-92 |
| eClass | 12 | 27-24-26-92 |
| eClass | 9.1 | 27-24-26-92 |
| eClass | 9 | 27-24-26-92 |
| eClass | 8 | 27-24-26-92 |
| eClass | 7.1 | 27-24-26-92 |
| eClass | 6 | 27-24-26-92 |
| ETIM | 10 | EC002584 |
| ETIM | 9 | EC002584 |
| ETIM | 8 | EC002584 |
| ETIM | 7 | EC002584 |

| | |
|---|---|
| **Approvals / Certificates** | |
| **General Product Approval** | |


© Copyright Plcbin

Manufacturer Declaration



**last modified:** 2/1/2026


Subject to change without notice
© Copyright Plcbin