SIEMENS

Data sheet 6ES7194-4AC00-0AA0



SIMATIC DP, connection module for PROFIBUS interface module ET 200 Pro; direct connection, integrated address setter and terminating resistor for PROFIBUS DP; product phase-out planned – see SIOS 109989704

Input current	
from supply voltage 1L+, max.	16 A
from load voltage 2L+ (without load), max.	16 A
Accessories	
Function description	Terminal module direct: PROFIBUS DP and 24 V power; up to 6 x M20 cable glands
belongs to product	ET 200pro; IM154-1/2 DP
Dimensions	
Width	90 mm
Height	130 mm
Depth	100 mm
Weights	
Weight, approx.	292 g
Classifications	

	Version	Classification
eClass	16	27-24-26-03
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration

© Copyright Plcbin

General Product Approval					Maritime application
EAC	KC	CE EG-Konf.	China RoHS	UKCA	ABS

Maritime application					
BUREAU VERITAS	DNV	Lloyd's Register LRS	NK / Nippon Kaiji Kyokai	RINA	CCS (China Classification Society)

Maritime application
KR (Korean Register of Shipping)

last modified: 4/7/2025

Subject to change without notice
© Copyright Plcbin