SIEMENS

Data sheet 6ES7221-1BH50-0XB0

Siemens EcoTech

SIMATIC S7-1200 G2: SM 1221 digital input, 16 DI; inputs: 16x DI 24 V DC sink/source



General information	
Product type designation	SM 1221, DI 16x 24 V DC
Input current	
from backplane bus 5 V DC, max.	90 mA
Digital inputs	
● from load voltage L+ (without load), max.	4.1 mA; per channel
Power loss	
Power loss, typ.	3.2 W
Digital inputs	
Number of digital inputs	16
● in groups of	4
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	16
— up to 50 °C, max.	16
vertical installation	
— up to 40 °C, max.	16
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	5 V DC or 0.5 mA
● for signal "1"	15 V DC at 2.5 mA
Input current	
● for signal "0", max. (permissible quiescent current)	0.5 mA
● for signal "1", min.	2.5 mA
● for signal "1", typ.	4.1 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
for interrupt inputs	
— Parameterizable	No
Cable length	
● shielded, max.	500 m
● unshielded, max.	300 m
Interrupts/diagnostics/status information	

© Copyright Plcbin

Diagnostics function	Yes
Alarms	
● Diagnostic alarm	No
Diagnoses	
● Monitoring the supply voltage	No
Diagnostics indication LED	
● for status of the inputs	Yes
● for maintenance	Yes
Potential separation	
Potential separation digital inputs	
● between the channels, in groups of	4
● between the channels and backplane bus	Yes; 707 V DC (type test)
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
CE mark	Yes
CSA approval	No
UL approval	Yes
cULus	Yes
FM approval	No
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	No
Ecological footprint	
● environmental product declaration	Yes; type 2 acc. to ISO 14021
Global warming potential	
— global warming potential, (total) [CO2 eq]	40.3 kg
— global warming potential, (during production) [CO2 eq]	7.79 kg
— global warming potential, (during operation) [CO2 eq]	32.5 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.089 kg
Ambient conditions	
Free fall	
● Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
● horizontal installation, min.	-20 °C
● horizontal installation, max.	60 °C; at max. voltages and max. specification
● vertical installation, min.	-20 °C
● vertical installation, max.	50 °C; at max. voltages and max. specification
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Air pressure acc. to IEC 60068-2-13	
● Operation, min.	540 hPa
● Operation, max.	1 140 hPa
● Storage/transport, min.	540 hPa
● Storage/transport, max.	1 140 hPa
Altitude during operation relating to sea level	
● Installation altitude, min.	-1 000 m
● Installation altitude, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Relative humidity	
● Operation at 25 °C without condensation, max.	95 %
Vibrations	
● Vibration resistance during operation acc. to IEC 60068-2-6	3.5 mm from 5 - 8.4 Hz, 1g from 8.4 - 150 Hz

© Copyright Plcbin

● Operation, tested according to IEC 60068-2-6	Yes
Shock testing	
● tested according to IEC 60068-2-27	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
Pollutant concentrations	
● SO2 at RH < 60% without condensation	S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free
Connection method	
required front connector	No
Mechanics/material	
Enclosure material (front)	
● Plastic	Yes
Dimensions	
Width	30 mm
Height	125 mm
Depth	100 mm
Weights	
Weight, approx.	166 g

Classifications

	Version	Classification
eClass	16	27-24-22-04
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration

General Product Approval

Manufacturer Declaration | China RoHS

EMV | **For use in hazardous locations**

Miscellaneous | CCC-Ex | CCC-Ex

Test Certificates | **Maritime application**

© Copyright Plcbin

Type Test Certific-ates/Test Report

ABS

BUREAU VERITAS

DNV

LRS

NK / Nippon Kaiji Ky-okai

Maritime application	Environment

RINA

KR (Korean Register of Shipping)

EPD

Siemens EcoTech

last modified: 10/23/2025

© Copyright Plcbin