SIEMENS

Data sheet 6ES7223-0BD30-0XB0



SIMATIC S7-1200, Digital I/O SB 1223, 2 DI/2 DO, 2 DI 24 V DC/2 DO 24 V DC

General information	
Product type designation	SB 1223, DI 2x24 V DC/DQ 2x24 V DC
Supply voltage	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, typ.	50 mA
Output voltage	
Power supply to the transmitters	
● Supply current, max.	4 mA; per channel
Power loss	
Power loss, typ.	1 W
Digital inputs	
Number of digital inputs	2; Current-sinking
● in groups of	1
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	2
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	0 to 5 V
● for signal "1"	+15 to +30 V
Input current	
● for signal "0", max. (permissible quiescent current)	1 mA
● for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
— at "0" to "1", max.	2 µs
— at "1" to "0", max.	10 µs
for interrupt inputs	
— Parameterizable	Yes
for technological functions	
— parameterizable	Yes
Cable length	
● shielded, max.	50 m
Digital outputs	

Subject to change without notice
© Copyright Plcbin

Number of digital outputs	2; MOSFET, solid-state (current-sinking/current-sourcing)
● in groups of	1
Short-circuit protection	No
Switching capacity of the outputs	
● with resistive load, max.	0.5 A
● on lamp load, max.	5 W
Load resistance range	
● upper limit	0.6 Ω
Output voltage	
● Rated value (DC)	24 V
● for signal "0", max.	0.1 V; with 10 kOhm load
● for signal "1", min.	20 V
Output current	
● for signal "1" rated value	0.5 A
● for signal "1" permissible range, max.	0.5 A
● for signal "0" residual current, max.	10 µA
Cable length	
● shielded, max.	50 m
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	
● for status of the inputs	Yes
● for status of the outputs	Yes
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ambient conditions	
Free fall	
● Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
● min.	-20 °C
● max.	60 °C
● horizontal installation, min.	-20 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-20 °C
● vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Air pressure acc. to IEC 60068-2-13	
● Storage/transport, min.	660 hPa
● Storage/transport, max.	1 080 hPa
Relative humidity	
● Operation at 25 °C without condensation, max.	95 %
Mechanics/material	
Enclosure material (front)	
● Plastic	Yes
Dimensions	
Width	38 mm
Height	62 mm
Depth	21 mm

© Copyright Plcbin

Weights

Weight, approx.	40 g

Classifications

	Version	Classification
eClass	16	27-24-22-04
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous

Manufacturer Declaration

General Product Approval

China RoHS

Manufacturer Declaration

EMV

For use in hazardous locations

For use in hazardous locations

FM

Miscellaneous

CCC-Ex

Maritime application

Maritime application

NK / Nippon Kaiji Kyokai

CCS (China Classification Society)

last modified: 7/2/2025

© Copyright Plcbin