SIEMENS

Data sheet 6ES7223-5BH50-0XB0

Siemens EcoTech

SIMATIC S7-1200 G2: SM 1223 digital I/O, 8 DI/8 DO inputs: 8x DI 24 V DC sink/source outputs: 8x DO, 24 V DC 0.5 A, sourcing transistor



Figure similar

General information	
Product type designation	SM 1223, DI 8x 24 V DC, DQ 8x 24 V DC 0.5A
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	110 mA
Digital inputs	
● from load voltage L+ (without load), max.	4.1 mA; per channel
Digital outputs	
● from load voltage L+, max.	45 mA
Power loss	
Power loss, typ.	4 W
Digital inputs	
Number of digital inputs	8
● in groups of	4
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	8
horizontal installation	
— up to 40 °C, max.	8
— up to 50 °C, max.	8
vertical installation	
— up to 40 °C, max.	8
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	5 V DC or 0.5 mA
● for signal "1"	15 V DC at 2.5 mA
Input current	
● for signal "0", max. (permissible quiescent current)	1 mA
● for signal "1", min.	2.5 mA
● for signal "1", typ.	4.1 mA
Input delay (for rated value of input voltage)	

© Copyright Plcbin

for standard inputs	
— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
for interrupt inputs	
— Parameterizable	No
Cable length	
● shielded, max.	500 m
● unshielded, max.	300 m
Digital outputs	
Number of digital outputs	8
● in groups of	8
Short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	typ. (L+) -40 V, 1 W dissipation
Switching capacity of the outputs	
● with resistive load, max.	0.5 A
● on lamp load, max.	5 W
Output voltage	
● Rated value (DC)	24 V
● for signal "0", max.	0.1 V; with 10 kOhm load
● for signal "1", min.	20 V DC
Output current	
● for signal "1" rated value	0.5 A
● for signal "1" permissible range, max.	0.5 A
● for signal "0" residual current, max.	10 µA
Output delay with resistive load	
● "0" to "1", max.	50 µs
● "1" to "0", max.	200 µs
Total current of the outputs (per group)	
horizontal installation	
— up to 50 °C, max.	2 A; Current per mass
Cable length	
● shielded, max.	500 m
● unshielded, max.	150 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
Diagnostics indication LED	
● DIAG LED	Yes
● for status of the inputs	Yes
● for status of the outputs	Yes
Potential separation	
Potential separation digital inputs	
● between the channels, in groups of	4
● between the channels and backplane bus	Yes; 707 V DC (type test)
Potential separation digital outputs	
● between the channels, in groups of	8
● between the channels and backplane bus	Yes; 707 V DC (type test)
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
CE mark	Yes
CSA approval	No
UL approval	Yes

© Copyright Plcbin

cULus	Yes
FM approval	No
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	No
Ecological footprint	
● environmental product declaration	Yes; type 2 acc. to ISO 14021
Global warming potential	
— global warming potential, (total) [CO2 eq]	40.3 kg
— global warming potential, (during production) [CO2 eq]	7.79 kg
— global warming potential, (during operation) [CO2 eq]	32.5 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.089 kg
Ambient conditions	
Free fall	
● Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
● horizontal installation, min.	-20 °C
● horizontal installation, max.	60 °C; at max. voltages and max. specification
● vertical installation, min.	-20 °C
● vertical installation, max.	50 °C; at max. voltages and max. specification
● permissible temperature change	5°C to 55°C, 3°C / minute
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Air pressure acc. to IEC 60068-2-13	
● Operation, min.	540 hPa
● Operation, max.	1 140 hPa
● Storage/transport, min.	540 hPa
● Storage/transport, max.	1 140 hPa
Altitude during operation relating to sea level	
● Installation altitude, min.	-1 000 m
● Installation altitude, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Relative humidity	
● Operation at 25 °C without condensation, max.	95 %
Vibrations	
● Vibration resistance during operation acc. to IEC 60068-2-6	3.5 mm from 5 - 8.4 Hz, 1g from 8.4 - 150 Hz
● Operation, tested according to IEC 60068-2-6	Yes
Shock testing	
● tested according to IEC 60068-2-27	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
Pollutant concentrations	
● SO2 at RH < 60% without condensation	S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free
Connection method	
required front connector	No
Mechanics/material	
Enclosure material (front)	
● Plastic	Yes
Dimensions	
Width	30 mm
Height	125 mm
Depth	100 mm
Weights	
Weight, approx.	170 g
Classifications	

	Version	Classification

© Copyright Plcbin

eClass	16	27-24-22-04
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419

Approvals / Certificates

General Product Approval

Miscellaneous

General Product Approval

China RoHS

EMV

For use in hazardous locations

Miscellaneous

For use in hazardous locations

CCC-Ex

CCC-Ex

Test Certificates

Type Test Certific-ates/Test Report

Maritime application

Maritime application

NK / Nippon Kaiji Ky-okai

KR (Korean Register of Shipping)

Environment

Environment

last modified: 10/23/2025

© Copyright Plcbin