SIEMENS

Data sheet 6ES7322-1HF01-0AA0



Figure similar

spare part SIMATIC S7-300, digital output SM 322, isolated, 8 DO (relay), 1x 20-pole, 24 V DC, 2 A or 230 V AC, 2 A

Supply voltage	
Load voltage L+	
● Rated value (DC)	24 V
Input current	
from supply voltage L+, max.	160 mA
from backplane bus 5 V DC, max.	40 mA
Power loss	
Power loss, typ.	3.2 W
Digital outputs	
Number of digital outputs	8; Relays
Short-circuit protection	No
Controlling a digital input	Yes
Switching capacity of the outputs	
● on lamp load, max.	50 W
● Low energy/fluorescent lamps with electronic control gear	10x 58 W
● Fluorescent tubes, conventionally compensated	1x 58 W
● Fluorescent tubes, uncompensated	10x 58 W
Output current	
● for signal "1" rated value	2 A
● for signal "1" minimum load current	5 mA
Parallel switching of two outputs	
● for uprating	No
● for redundant control of a load	Yes
Switching frequency	
● with resistive load, max.	2 Hz
● with inductive load, max.	0.5 Hz
● With inductive load (to IEC 60947-5-1, DC13/AC15), max.	0.5 Hz
● on lamp load, max.	2 Hz
● mechanical, max.	10 Hz
Relay outputs	
● Rated supply voltage of relay coil L+ (DC)	24 V; 110 mA
● Contact connection (internal)	Yes; SIOV-CU4032 K275G
● Number of operating cycles, max.	300 000; 230 V AC: 100 000; 120 V AC: 200 000; 24 V DC: 300 000 (at 2 A)
Switching capacity of contacts	
— with inductive load, max.	2 A; 2 A (230 V AC), 2 A (24 V DC)
— with resistive load, max.	2 A
— Thermal continuous current, max.	3 A
Cable length	

© Copyright Plcbin

● shielded, max.	1 000 m
● unshielded, max.	600 m
Interrupts/diagnostics/status information	
Alarms	No
Diagnostics function	No
Alarms	
● Diagnostic alarm	No
Diagnoses	
● Wire break	No
● short-circuit	No
● Fuse blown	No
● Missing load voltage	No
Diagnostics indication LED	
● Rated load voltage PWR (green)	No
● Fuse OK FSG (green)	No
● Status indicator digital output (green)	Yes
Potential separation	
Potential separation digital outputs	
● between the channels	Yes
● between the channels, in groups of	2
● between the channels and backplane bus	Yes; Optocoupler
Isolation	
Isolation tested with	1 500 V AC
Connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	190 g

Classifications

	Version	Classification
eClass	16	27-24-22-04
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration

General Product Approval	EMV

Subject to change without notice
© Copyright Plcbin

China RoHS

Manufacturer Declaration

For use in hazardous locations	Maritime application
FM	ABS, BUREAU VERITAS, DNV, LRS, NK / Nippon Kaiji Kyokai

Maritime application
PRS, RINA, CCS (China Classification Society)

last modified: 4/7/2025

© Copyright Plcbin