SIEMENS

Data sheet 6ES7400-1TA11-0AA0

SIMATIC S7-400, rack UR1 Alu, central and distributed with 18 slots, 2 redundant PS can be plugged in



Figure similar

General information	
Product type designation	UR1
Hardware configuration	
Rack	
● Communication bus	Yes
● P bus	Yes
Slots	
● Number of slots	18
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
UL approval	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
CCC	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	60 °C
Ambient temperature during storage/transportation	
● min.	0 °C
● max.	70 °C
Mechanics/material	
rack profile material	aluminum
Dimensions	
Width	482.5 mm
Height	290 mm
Depth	27.5 mm
Weights	
Weight, approx.	3 kg
Classifications	

	Version	Classification
eClass	16	27-24-22-03
eClass	14	27-24-22-03
eClass	12	27-24-22-03

Subject to change without notice
© Copyright Plcbin

eClass	9.1	27-24-22-03
eClass	9	27-24-22-03
eClass	8	27-24-22-03
eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

Manufacturer Declaration

Miscellaneous

General Product Approval

China RoHS

Miscellaneous

Manufacturer Declaration

EMV

For use in hazardous locations

Declaration of Conformity

FM

For use in hazardous locations

Type Examination Certificate

Maritime application

Maritime application

NK / Nippon Kaiji Kyokai

CCS (China Classification Society)

Environment

last modified: 6/7/2025

© Copyright Plcbin