SIEMENS

Data sheet 6ES7403-1JA01-0AA0



SIMATIC S7-400, extension rack ER2 with 9 slots, only for signal modules 2 redundant PS can be plugged in

General information	
Product type designation	ER2
Hardware configuration	
Rack	
● Communication bus	No
● P bus	Yes
Slots	
● Number of slots	9
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
UL approval	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
CCC	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	60 °C
Ambient temperature during storage/transportation	
● min.	0 °C
● max.	70 °C
Dimensions	
Width	257.5 mm
Height	290 mm
Depth	27.5 mm
Weights	
Weight, approx.	2 200 g
Classifications	

	Version	Classification
eClass	16	27-24-22-03
eClass	14	27-24-22-03
eClass	12	27-24-22-03
eClass	9.1	27-24-22-03
eClass	9	27-24-22-03

© Copyright Plcbin

eClass	8	27-24-22-03
eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

Miscellaneous

General Product Approval | EMV | For use in hazardous locations

China RoHS | Miscellaneous | Manufacturer Declaration

For use in hazardous locations

Declaration of Conformity | FM | Type Examination Certificate

For use in hazardous locations | Maritime application

NK / Nippon Kaiji Kyokai

Maritime application | Environment

CCS (China Classification Society)

last modified: 6/7/2025

© Copyright Plcbin