SIEMENS

Data sheet 6ES7505-0KA00-0AB0



SIMATIC S7-1500, System power supply PS 25W 24 V DC, supplies the backplane bus of the S7-1500 with operating voltage

General information	
Product type designation	PS 25W 24VDC
HW functional status	from FS01
Firmware version	from V1.0.0
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V12 / V12
● STEP 7 configurable/integrated from version	V5.5 SP3 or higher
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V; Static 19.2 V, dynamic 18.5 V
permissible range, upper limit (DC)	28.8 V; Static 28.8 V, dynamic 30.2 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
● Mains/voltage failure stored energy time	20 ms
Input current	
Rated value at 24 V DC	1.3 A
Output current	
Short-circuit protection	Yes
Power	
Infeed power to the backplane bus	25 W
Power loss	
Power loss at nominal rating conditions	6.2 W
Interrupts/diagnostics/status information	
Status indicator	Yes
Potential separation	
primary/secondary	Yes
Isolation	
Isolation tested with	707 V DC (type test)
EMC	
Interference immunity against voltage surge	
● Interference immunity on supply lines acc. to IEC 61000-4-5	Yes; ±1 kV (acc. to IEC 61000-4-5; 1995; surge symm.), ±2 kV (acc. to IEC 61000-4-5; 1995; surge asymm.), no external protective circuit required
Degree and class of protection	
Equipment protection class	III, with protective conductor
Ambient conditions	
Ambient temperature during operation	
● min.	-25 °C; up to FS03: 0 °C
● max.	60 °C

© Copyright Plcbin

● horizontal installation, min.	-25 °C; up to FS03: 0 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-25 °C; up to FS03: 0 °C
● vertical installation, max.	40 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	350 g

Classifications

	Version	Classification
eClass	16	27-24-22-09
eClass	14	27-24-22-09
eClass	12	27-24-22-09
eClass	9.1	27-24-22-09
eClass	9	27-24-22-09
eClass	8	27-24-22-09
eClass	7.1	27-24-22-09
eClass	6	27-24-22-09
ETIM	10	EC000599
ETIM	9	EC000599
ETIM	8	EC000599
ETIM	7	EC000599
IDEA	4	3575
UNSPSC	15	32-15-17-06

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration

General Product Approval

BIS CRS | Manufacturer Declaration

General Product Approval	For use in hazardous locations			
China RoHS	FM	FM	CCC-Ex	

For use in hazardous locations

© Copyright Plcbin

IECEx

ATEX

Type Examination Certificate

Miscellaneous

UKCA

CCC-Ex

Maritime application

ABS

BUREAU VERITAS

DNV

LRS

NK / Nippon Kaiji Kyokai

RINA

Maritime application

RMRS

CCS (China Classification Society)

KR (Korean Register of Shipping)

last modified: 10/23/2025

Subject to change without notice
© Copyright Plcbin