SIEMENS

# Data sheet for SINUMERIK 828 PPU 271.4

**Article No. :** **6FC5370-5AA40-0AA0**




Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

## Rated data

| | |
|---|---|
| Input voltage | DC 24 V +20 % -15 % |
| Power consumption, max. | 60 W |

## Mechanical data

| | |
|---|---|
| Mounting position | Horizontal |
| Operator panel | Vertical |
| Net weight | 4.50 kg (9.92 lb) |
| Width | 483.0 mm (19.02 in) |
| Height | 220.0 mm (8.66 in) |
| Depth | 105.0 mm (4.13 in) |

**Degree of protection**

| | |
|---|---|
| Front side | IP65 With the front flap closed |
| Rear side | IP20 / UL open type |

## General tech. specifications

| | |
|---|---|
| Mains buffering time | 3 ms, 20 ms mit SITOP smart power supply |

## Ambient conditions

**Ambient temperature**

| | |
|---|---|
| Operation on the front | 0 ... 45 °C (32 ... 113 °F) |
| Operation at the rear | 0 ... 55 °C (32 ... 131 °F) |
| Storage | -25 ... 55 °C (-13 ... 131 °F) |
| Transport | -20 ... 60 °C (-4 ... 140 °F) |

**Relative humidity**

| | |
|---|---|
| Operation | 5 ... 90 % |
| Storage | 10 ... 100 % |
| Transport | 5 ... 95 % |